



Insulation Certificate for Residential New Construction

Permit #:	
House address or lot number:	
Walls	Blown or Sprayed Fiberglass or Cellulose - Walls
Type of insulation:	R-Value per Inch:
Manufacturer:	Coverage Area:
R-Value:	Bag Count:
Floor	Blown or Sprayed Fiberglass or Cellulose - Ceiling
Type of insulation:	R-Value per Inch:
Manufacturer:	Coverage Area:
R-Value:	Bag Count:
Flat Ceiling/Attic	Sprayed Polyurethane Foam (SPF)
Type of insulation:	Density:
Manufacturer:	Installed Thickness:
R-Value:	R-Value of Installed Thickness
	Building Component Installed: walls floor ceiling
Single Rafter Joist Vaulted Ceiling	
Type of insulation:	
Manufacturer:	
R-Value:	
Insulation Installer:	
Company Name:	Installer:
Installer Signature:	Date:
Phone Number:	

Washington State Energy Code Reference http://www.energy.wsu.edu/Documents/2012%20Res%20Energy.pdf:

R303.1 Identification. Materials, systems and equipment shall be identified in a manner that will allow a determination of compliance with the applicable provisions of this code.

R303.1.1 Building thermal envelope insulation. An R-value identification mark shall be applied by the manufacturer to each piece of building thermal envelope insulation 12 inches (305 mm) or greater in width. Alternately, the insulation installers shall provide a certification listing the type, manufacturer and R-value of insulation installed in each element of the building thermal envelope. For blown or sprayed insulation (fiberglass and cellulose), the initial installed thickness, settled thickness, settled R-value, installed density, coverage area and number of bags installed shall be listed on the certification. For sprayed polyurethane foam (SPF) insulation, the installed thickness of the areas covered and R-value of installed thickness shall be listed on the certification. The insulation installer shall sign, date and post the certification in a conspicuous location on the job site.